




## TRIPOD TURNSTILES

# LTT 323D



### TECHNICAL SPECIFICATIONS

<b>Operation</b>	Adjustable manual passage to either direction	<b>Power Consumption</b>	10 W during passages, 14 W during stand-by 
<b>Frame</b>	Two-legged, AISI 304 quality stainless steel, Optional: AISI 316 quality	<b>Operating Temperature</b>	-10° / +70° Optional: with heater -40°
<b>Core Arms</b>	CNC-machined, aluminum cast core and polished Ø40x2.5mm aluminum arms Optional: Stainless Steel Arms	<b>Passage Speed</b>	~50 persons/minute
<b>Functions</b>	Passage information (NC or NO), passage time, memory mode, audio warning, adjustable passage direction	<b>Passage Width</b>	45 – 50 cm
<b>Mechanism</b>	AISI 304 quality stainless steel. Fail-Safe (arms drop during power failure) Optional: Fail lock	<b>Weight</b>	~52 kg
<b>Emergency Mode</b>	The arms fall down with the signal received from fire detection system. Optional: Drop Arm	<b>Security Level</b>	Deterrent
<b>Operating Voltage</b>	100-230 VAC, 47-60 Hz	<b>Indicators</b>	Direction LEDs for both directions.
		<b>Areas of Use</b>	Suitable for indoor use (Can be used outdoors with its cover)
		<b>Accessories</b>	Outdoor cover, Unauthorized Passage Notification System, Meter, Button Control Unit, Remote Control Unit, Stainless Steel Bottom Plate, Plexiglass Reader Assembly Kit, Reader Assembly Apparatus, RS232 Communication Unit.